

## MATERIAL SAFETY DATA SHEET

AMERICAN COATINGS CORPORATION  
3037 NW 60th STREET  
FT. LAUDERDALE, FL 33309  
(954)970-7820

EMERGENCY TELEPHONE  
(800) 533-0151

DATE OF PREPARATION  
November 14, 2005

### SECTION I - PRODUCT INFORMATION

|  |                               |      |   |
|--|-------------------------------|------|---|
| PRODUCT NAME: NoBee-300                                    | TRADE NAME: Soy Methyl Esters |      |   |
| TRANSPORTATION INFORMATION:<br>Cleaning Compound, Class 55 |                               | HMIS |   |
|  | Health                        |      | 0 |
|  | Flammability                  |      | 1 |
| HAZARD CLASS: Not regulated                                | Reactivity                    |      | 0 |

### SECTION II - INGREDIENTS

| INGREDIENT                         | Percent | Exposure Limits |     |
|------------------------------------|---------|-----------------|-----|
|                                    |         | TLV             | PEL |
| Methyl Esters<br>[67762-38-3]      | >90     | Not established |     |
| Nonionic surfactant<br>[9016-45-9] | <10     | Not established |     |

### SECTION III - PHYSICAL DATA

|                          |                        |                   |                |
|--------------------------|------------------------|-------------------|----------------|
| BOILING POINT:           | > 400°F                | VAPOR PRESSURE:   | < 5 mmHg       |
| VAPOR DENSITY: (Air = 1) | n/a                    | WATER SOLUBILITY: | Minimal        |
| SPECIFIC GRAVITY:        | .88                    | PERCENT VOLATILE: | n/a            |
| EVAPORATION RATE:        | Slow                   | APPEARANCE:       | Clear to amber |
| ODOR:                    | Typical bean/vegetable |                   |                |

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: FLASH POINT: > 300°F (PMCC) LEL: N/A UEL: N/A

EXTINGUISHING MEDIA: Carbon dioxide, foam, dry chemical. Water spray may be ineffective.

SPECIAL FIREFIGHTING PROCEDURE: Water spray may be used to cool drums.

COMBUSTION PRODUCTS: Carbon monoxide with incomplete combustion.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Firefighters should use self contained breathing apparatus.

---

## SECTION V - HEALTH HAZARD DATA

---

TLV: Not established

**HEALTH HAZARD FROM ACUTE EXPOSURE:**

Inhalation: Minimal unless heated. Vapors may irritate mucous membranes.

Eyes: May cause irritation.

Skin: Not likely to cause skin irritation from prolonged contact.

**EMERGENCY AND FIRST AID PROCEDURE:** Skin - wash with soap and water. Eyes - Flush eyes with water 15-20 minutes. Contact physician if condition persists. Inhalation - Remove to fresh air. Get medical attention. Ingestion - Drink 1 or 2 glasses of water. Consult medical attention. Never give anything by mouth if victim is unconscious.

---

## SECTION VI - REACTIVITY DATA

---

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: No decomposition up to 350° F.

CONDITIONS TO AVOID: None described

INCOMPATIBILITY (Materials to Avoid): Oxidizing agents, strong bases.

---

## SECTION VII - SPILL OR LEAK PROCEDURES

---

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Contain to small area. Control leak. Collect with absorbent materials. Eliminate all sources of ignition. Wash area thoroughly. Slippery on floors.

**WASTE DISPOSAL METHOD:** In accordance with all applicable regulations.

---

## SECTION VIII - SAFE HANDLING AND USE INFORMATION

---

**RESPIRATORY PROTECTION:** If vapor levels become high, use NIOSH approved respirators.

**VENTILATION:** Provide adequate ventilation.

**PROTECTIVE GLOVES:** PVC gloves.

**EYE PROTECTION:** Goggles, face shields, or other eyewear to protect from splash. As a general rule, contact lens should not be worn when working with chemicals.

**OTHER PROTECTIVE EQUIPMENT:** Oil resistant apron/clothing, emergency eye wash and shower stations.

**HYGIENIC PRACTICES:** Wash thoroughly after handling. Launder used clothing before reuse.

---

## SECTION IX - SPECIAL PRECAUTIONS

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store between 50°F and 120°F. Store and use with sufficient ventilation. Store out of the sun. Avoid oxidizing agents, ignitable sources and excessive heat.

The information described herein is to the best of American Coatings' knowledge accurate as of the date this has been issued. American Coatings makes no warranty expressed or implied regarding this information's accuracy or reliability; moreover, American Coatings shall not be held liable for any losses/damages which may be construed to have developed from this information. It is the users responsibility to determine the suitability of this product for each project onto which it is intended to be used.